

ML-SR-29



Referece	ML-SR-29
	WIRED BEACON MONOCOLOR AND RBG OPTION

Advantages	
Advantages	Cabling system for connection to main network or Solar. Designed for marking roads, tunnels. High brightness day and night. IP67 LEDs protected by polycarbonate window. unidirectional or bidirectional operation
Working Modes	Fix- Flashing - Fix - Sequential

ELECTRICAL FEATURES					
Output	12 / 24Vdc				
Led Colours	Amber	Red	White	Blue	Green
Power consumption	40 mA (Unidireccional) 80 mA (Bidireccional)				
CONEXION CABLES					
Brown- Red	(+)				
Blue	(-)				
LED NUMBER					
LED NUMBER	6 Leds (unidirectional) - 12 Leds (bidireccional)				
LED	RGB		RGB		STANDARD (1 color)
Color Led	Amber	Red	White	Blue	Green
Angle	15°	15°	15°	15°	15°
Aprox Lifetime	100.000 hours				
Brightness / led	Min: 8200mcd Max:16800mcd	Min.: 8200mcd Max:16800mcd	Min:22000mcd Max:31000mcd	Min.: 6960mcd Max: 9750mcd	Min:15320mcd Max:21650mcd
DIMENSIONS					
Dimensions	Diámetro: 145 mms.				
Height	42 mm				
Maximun height once installed	13 mm (parable center)				
Installation Depth	29 mm				
Visible Surface	145 mm diameter				
Stud Material	Aluminium- Policarnate window				
Mecanical Strenght	30 Ton				









