



<b>Reference:</b>	<b>ML-TR-25</b>
<b>Functional Characteristics:</b>	<b>Road Stud Pedestrian Crosses, Guiding, Signalling.</b>

### TECHNICAL FEATURES

<b>Work Mode:</b>	<b>Fix - (Flashing / Secuential controller required)</b>
-------------------	--

### ELECTRICAL CHARACTERISTICS

<b>Voltage:</b>	<b>12 / 24Vdc</b>					
<b>Led Colors:</b>	<b>Amber</b>	<b>Red</b>	<b>White</b>	<b>Blue</b>	<b>Green</b>	<b>RGY</b>

### OPTICAL CHARACTERISTICS

<b>LEDS Nº:</b>	<b>2 x 2 leds Vehicles, 2 x 3 leds Pedestrian. Total nº: 10 Leds</b>
-----------------	--

### MECHANICAL CHARACTERISTICS

<b>Dimensions:</b>	<b>Diameter:138 mms</b>
<b>Height:</b>	<b>66 mms</b>
<b>Maximun Height from ground:</b>	<b>15mms</b>
<b>Enclouser Material:</b>	<b>Aluminium ADC10</b>
<b>Material:</b>	<b>Aluminium/ Policarbonate</b>
<b>Mechanical Resistance:</b>	<b>3tn (30Kn)</b>

