

ML-TR-29 SOLAR - Baliza Solar Led Stud



TECHNICAL FEATURES - Advantages

- **Projected** for road marking, tunnels.
- **High brightness** day and night
- **IP68.**
- **LEDs protected** by polycarbonate window.
- Unidirectional or bidirectional **operation.**
- **Operating modes Fixed** – Intermittent (2HZ)

ELECTRIC FEATURES

- **Power:** Monocrystalline Solar Panel 3,5v-80ma
- **Consumption:** 40ma(Unidirectional) 80ma (Bidirectional)
- **Automatic power on:** < 300 lux

SOLAR PANEL & BATTERY

- **Monocrystalline Solar Panel** 3,5v-120Mah
- **Battery:** NI-MH 600MAh-2.4v- **Autonomy:** 120 Hours- **Fix Mode.**

MECHANICAL FEATURES

- **Dimensions:**
Diameter: 145mm-Height 44mm.
- **Maximun Height on Surface:** 15 mms.
- **Embeded Depth:** 50 mms.
- **Visible Surface:** 145 mms.
- **Material:** Aluminim
- **Polycarbonate Cover and Lens**
- **Weight:** 0,7 Kg.
- **Resistance:** 35 TN
- **IP68**
- **Visibility:** Hasta 800 m.
- **Working temperature:** - 35°C / 80° C

OPTICAL FEATURES

- **Leds Number:**
 - 3 Led (Unidirectional)
 - 6 Led (Bidirectional)
- **Led:** 5 mm
- **Angle:** 35°
- **Led Color / Intensity:**
 - Ámber (5000 mcd)
 - Red (5000 mcd)
 - White (8000 mcd)
 - Blue (2800 mcd)
 - Green (6000 mcd)



