

## SEMAFORO ML-200 CLASIC

### FICHA TÉCNICA



El modelo está fabricado, con resinas de policarbonato LEXAN®103R del fabricante G.E. plastics UV estabilizado, y disponible en cuerpos de 200mm., diferentes combinaciones de tamaños y formatos.



*The model is made with polycarbonate resins manufacturer GE LEXAN®103R plastics UV estabilized, and available bodies. 200mm., different combinations of sizes and formats.*



### CARACTERÍSTICAS / FEATURES

DIAMETRO DIAMETER	MODULOS MODULES	DIMENSIONES DIMENSIONS width / height / depth	COLORES COLORS	TEMPERATURA TEMPERATURE	RESISTENCIA RESISTANCE	CERTIFICADO CE CE CERTIFICATE
200mm.	1	265 / 255 / 160 (380*)	NEGRO / BLACK:	A, B and C (-40°C / +65°C) in compliance with PN-EN 12368:2006	IR3 in compliance with PN-EN 12368:2006	Full conformity with PN-EN 12368:2006
	2	265 / 510 / 160 (380*)	AMARILLO/YELLOW: GRIS / GREY:	RAL 9005 RAL 1003 RAL 7032 RAL6009		
	3	265 / 765 / 160 (380*)	VERDE / GREEN:			

\* medida con visera / depth with visors

Complete waterproofness: Class IP55

