

FICHA TÉCNICA DATASHEET



ML-ST-CLASIC

El modelo está fabricado, con resinas de policarbonato LEXAN®103R del fabricante G.E. plastics UV estabilizado, y disponible en cuerpos de 200mm., diferentes combinaciones de tamaños y formatos.

The model is made with polycarbonate resins manufacturer GE LEXAN®103R plastics UV estabilized, and available bodies. 200mm., different combinations of sizes and formats.

CARACTERÍSTICAS / FEATURES

DIAMETRO DIAMETER	MODULOS MODULES	DIMENSIONES DIMENSIONS width / height / depth	COLORES COLORS	TEMPERATURA TEMPERATURE	RESISTENCIA RESISTANCE	CERTIFICADO CE CE CERTIFICATE
100mm.	1	160 / 145 / 210*	NEGRO / BLACK:	RAL 9005	A,B and C (-40°C / +65°C) in compliance with PN-EN 12368:2006	IR3 in compliance with PN-EN 12368:2006
	2	160 / 290 / 210*	AMARILLO/YELLOW:	RAL 1003		
	3	160 / 435 / 210*	GRIS / GREY: VERDE / GREEN:	RAL 7032 RAL6009		

* medida con visera / depth with visors

Complete waterproofness: Class IP55

